



TECHNICAL DATA

QUICK-DRY SANDING SEALER #8065 CLEAR SATIN FINISH

DESCRIPTION

Recommended Uses:

Cabot Quick-Dry Sanding Sealer is uniquely formulated to seal interior bare and stained wood surfaces including doors, furniture, woodwork, cabinets and shelves. The clear, satin finish enhances the natural wood grain. Use under oil-based varnishes or polyurethanes to ensure a smoother topcoat appearance. It dries quickly and can be recoated in just one hour.

Do not use on floors.

Composition:

Hydrocarbon Resin and Vinyl Toluene Modified Alkyd

Finish:

This product penetrates and seals the surface. Provides excellent resistance to sandpaper gumming.

Color:

Clear Satin

Tinting/Intermixing:

Cabot Quick-Dry Sanding Sealer cannot be tinted or intermixed with any other product.

Coverage/Thinning:

One gallon covers up to 400-500 sq. ft. (37-46 m²) depending upon surface porosity. Do not thin.

One quart covers up to 100-125 sq. ft. (9.3-11.6 m²) depending upon surface porosity. Do not thin.

Packaging/Containers:

Available in quart and gallon containers

Restrictions:

Not intended for use on floors.

For interior use only.

TECHNICAL DATA

Environmental Impact:

These products are in compliance with V.O.C. (Volatile Organic Compounds) requirements for Specialty Architectural Coatings under current regulations. Call Cabot's Technical Services & Support for additional information pertaining to current V.O.C. rulings.

**WARNING! VAPOR HARMFUL.
COMBUSTIBLE LIQUID & VAPOR.**

**DANGER: CONTAINS VM & P NAPHTHA
AND MINERAL SPIRITS. FLAMMABLE:**

DO NOT SMOKE. Keep away from sparks, open flame, and lit cigarettes. Turn off stoves, heaters, electric motors, pilot lights and other sources of ignition during use and until all vapors are gone. Prevent build up of vapors by opening all windows and doors for cross ventilation.

**Emergency Medical Telephone:
1-888-345-5732**

Cleanup and Disposal: Clean brushes and equipment with mineral spirits. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spillage, absorb with inert material such as sand or kitty litter.

Dispose of empty cans or unused portion in accordance with local, state and federal regulations. Material Safety Data Sheets (MSDS) are available upon request.

DANGER: Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after each use, place rags, steel wool or waste in a sealed, water-filled metal container and dispose of according to local regulations.

Physical and Chemical Data:

Drying Time: Dries to the touch in 15-30 minutes. Wait 1 hour before sanding and recoating. Dry times are longer in high humidity or cool temperatures. Apply only when surface and air temperatures are between 50-90°F (10-32°C) during application and drying time.

Weight: 7.2+/-0.1 pounds per gallon.

Flash Point: 61°F (16°C)

Film Thickness: Nil after sanding

Shelf Life: A minimum of five (5) years in closed original containers.

% Solids (weight): 41+/-1.0

% Solids (volume): 33.0+/-1.0

% Pigment (weight): 1.5

Viscosity: 50-150 cps.

Pigment Type: Precipitated Silica, Stearates

Vehicle Type: Hydrocarbon resin, VT modified alkyd

Solvent Type: Aliphatic Hydrocarbons

V.O.C. Content: GPL Maximum of 550 grams/liter (4.6 pounds/gallon)

QUICK-DRY SANDING SEALER #8065 CLEAR SATIN FINISH

APPLICATION

Surface Preparation:

General: Clean and dry surface thoroughly, removing all dirt, dust, wax and wood marks. Do not use over sealed wood or on floors.

New or Stained Wood: Smooth wood lightly with sandpaper. Stain, if desired, and sand lightly again. Remove sanding dust before finishing.

Painted or Varnished Wood: Remove all paint and varnish in poor condition with sandpaper or paint and varnish remover following manufacturer's instructions and safety precautions. Then, follow new wood instructions.

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the USEPA/Lead Information Hotline at 1-800-424-LEAD (5323) or visit www.epa.gov/lead.

Wood surfaces must be clean, free of sanding dust, wax, grease, old finishes, mildew stains or other contaminants. Surfaces must be absolutely dry (moisture below 15%). Fill nail holes with high-quality wood putty. Sand surface to the desired smoothness using progressively finer grades of sandpaper to remove all scratches and nicks.

Application:

DO NOT SHAKE! Stir well before use and occasionally during use. Before applying the finish to the entire surface, check effect by testing on an extra piece of the same wood or by applying to a hidden part of the object. Apply a uniform, thin coat using a high quality, clean polyester or natural bristle brush. **Two coats are recommended.** Brush in even strokes in the direction of the wood grain. Allow the first coat to dry 1 hour and sand lightly with fine sandpaper to remove any grain raise. Remove all sanding dust before applying the second coat. Allow to dry 1 hour before topcoating, if desired. For maximum durability, finish with one or two coats of Cabot® Oil-Based Varnish or Polyurethane, following the label instructions.

AVAILABILITY

Cabot Wood Care Products are sold throughout the United States and Canada. For a list of Cabot dealer locations, please contact Cabot's Technical Services & Support at 1-800-US-STAIN.

WARRANTY

If this product does not perform as stated on the label after you apply it according to label directions, Cabot will either replace this product or refund its purchase price, at its option. Cabot disclaims all other implied or expressed warranties. Cabot will not provide or pay for labor for removal or application of the product. This warranty excludes all incidental or consequential damages. This warranty gives you specific legal rights, and you may have other rights which vary from state to state.

MAINTENANCE

Cabot Quick-Dry Sanding Sealer does not require a maintenance schedule.

TECHNICAL SERVICES

For additional technical information see your specialized Cabot dealer or call Cabot's Technical Services & Support toll-free at 1-800-US-STAIN (877-8246).

FILING SYSTEMS

For complete model specifications and technical data on all Cabot products, visit the Cabot Home Page at: cabotstain.com.



Cabot®
Newburyport, MA 01950
Tel.: 800-US-STAIN
Fax: 1-800-998-3299
cabotstain.com